

## Product Code

Family code	11001F
Order code	LV-LUR11001-SSB4WIP673K10N

## Technical data

Mounting	Recessed
Installation Position	Inground
Light Source	LED
Consumption	2x2W
LED Source lumens	560 Lm
Delivered lumens	480 Lm
Luminaire luminous efficiency	140 Lm/W
Colour temperature	3000K
Colour rendering index index ty	Ra≥90
Beam angle (At 50% of Imax)	8° / 15° / 25° / 35° / 45°
LED power supply unit	AC220V
Warranty	5 Years
Life Span	50 000 Hrs

## Surface Finishing

Material	Aluminium / Tempered step glass T=4mm
Body Colour	Stainless Steel 316
Reflector Colour	Black

## Optical and Visual Confort

Optical Type	Diffuser
SDCM	≤3
Light Distribution Symmetry	Symmetry
Optical cover material	PC

## Product Image



## Dimensions



## LED

LED brand	CREE
LED Model Type.	SMD

## Driver

Driver brand	OSRAM
THD	≤ 20 %
Driver output	/
Driver efficiency	≥ 94
Power Factor	> 0.95
Dimming	On/Off - Dali Customized

## Safety and Compliance

Protection class IP	IP67
Impact Protection	IK10
Installation Environment	Outdoor
Safety	CLASS I
Ambient temperature	-40 +60° C

## Product simulation



## Light distribution

